

# Facit och kommentarer till tenta 2024-03-07 i DA2004 och DA2005

## Del A

1. A, B, C
2. A
3. C
4. E
5. E
6. D
7. C
8. A

## Del B

### Del B: kodfrågor

9.
  - The return value is a list, not a string.
  - The *i* variable is global. Python will actually signal an error because a global variable is assigned without having a **global i** statement. But even if one got that right, the function will not function correctly in subsequent calls.

```
10. def rev(string_to_reverse):  
    '''  
        Return the input string, but reversed.  
    '''  
    if s == '':  
        raise ValueError('Empty string given to rev')  
    reversed_s = ''  
    for char in string_to_reverse:  
        reversed_s = char + reversed_s  
    return reversed_s
```

11. First suggestion, a compact function using list comprehension:

```
def monotonic(lst):  
    lst1 = lst[:-1]  
    lst2 = lst[1:]  
    diffs = [e1 - e2 for (e1, e2) in zip(lst1, lst2)]  
    return all(diff >= 0 for diff in diffs) or all(diff <= 0 for diff in diffs)
```

Second suggestion, using a function in the standard library:

```
def monotonic2(lst):  
    if lst == sorted(lst):  
        return True  
    elif lst == sorted(lst, reverse=True):  
        return True  
    else:  
        return False
```

```
12. def loan_analysis(initial_loan, monthly_payment, yearly_interest):  
    loan = initial_loan  
    month = 0  
    while loan > monthly_payment:  
        month += 1  
        interest = round(loan * yearly_interest / 12, 2)  
        loan = round(loan + interest - monthly_payment, 2)  
        print(month, loan, interest)
```

```
13. class Table:
    def __init__(self):
        self._ldict = {}
        self._rdict = {}

    def add(self, key, val):
        self._ldict[key] = val
        self._rdict[val] = key

    def items(self):
        return self._ldict.items()

    def get(self, key):
        if key in self._ldict:
            return self._ldict[key]
        elif key in self._rdict:
            return self._rdict[key]
        else:
            raise KeyError(f"'{key}' is not found in the table")

    def __repr__(self):
        return str(self)
    def __str__(self):
        return f'<Table {str([(a, b) for a, b in self._ldict.items()])}>'
```